SDS Number: 60982

2

Revision Date: 6/24/2019

1	PRODUCT AND COMPANY IDENTIFICATION
Vendor Performance Diesel, LLC 251 King Muir Rd. Lake Forest, IL 60045	
Phone:	847-565-8150
Emergency:	1-800-424-9300 (Chemtrec)
Product Identifier: Synonyms: SDS Number: Product Code: Revision Date: CAS Number:	Performance Antigel Deicer Formula Diesel Fuel Additive 60982 60982 6/24/2019 Blend

HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):

Physical, Flammable Liquids, 3 Health, Skin corrosion/irritation, 2 Health, Serious Eye Damage/Eye Irritation, 2 A Health, Specific target organ toxicity - Single exposure, 3 Health, Acute toxicity, 4 Dermal Health, Acute toxicity, 4 Inhalation Health, Acute toxicity, 4 Oral Health, Carcinogenicity, 2 Environmental, Hazards to the aquatic environment - Chronic, 2

GHS Label Elements, Including Precautionary Statements

GHS Signal Word: WARNING

GHS Hazard Pictograms:



GHS Hazard Statements:

- H226 Flammable liquid and vapour
- H315 Causes skin irritation
- H319 Causes serious eye irritation
- H335 May cause respiratory irritation
- H336 May cause drowsiness or dizziness
- H312 Harmful in contact with skin
- H332 Harmful if inhaled
- H302 Harmful if swallowed
- H351 Suspected of causing cancer.
- H411 Toxic to aquatic life with long lasting effects

GHS Precautionary Statements:

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

- P233 Keep container tightly closed.
- P240 Ground and bond container and receiving equipment.
- P241 Use explosion-proof [electrical/ventilating/lighting] equipment.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P273 Avoid release to the environment.

SDS Number: 60982

Revision Date: 6/24/2019

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER/doctor/...

SUS

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do Continue rinsing.

P308 + P313 - IF exposed or concerned: Get medical advice/ attention.

3

6

COMPOSITION/INFORMATION OF INGREDIENTS

	Chem	ical Ingredients:
CAS#	%	Chemical Name:
64742-95-6	50-60%	Solvent naphtha, petroleum, light arom.
95-63-6	<20%	1,2,4-Trimethylbenzene
111-76-2	<15%	2-Butoxyethanol
1330-20-7	<2%	Xylene
98-82-8	<1%	Cumene

4 FIRST AID MEASURES

Inhalation:	If symptoms develop, move victim to fresh air. If symptoms persist, obtain medical attention.
Skin Contact:	Wash with soap and water. Remove contaminated clothing and wash before reuse. Get medical attention if needed.
Eye Contact:	Flush with water for several minutes. If effects occur, consult a physician.
Ingestion:	Rinse mouth with water and drink 2-4 cups of water. Get immediate medical attention. Note to Physician: Activated charcoal may be administered.

5 FIRE FIGHTING MEASURES

Flash Point: >46 C (>115 F)

Use dry powder, foam, or carbon dioxide fire extinguishers. Water may be ineffective unless used by experienced fire fighters.

ACCIDENTAL RELEASE MEASURES

Eliminate sources of ignition - Heat, sparks, flame, and electricity Contain spilled material.

Collect in suitable and properly labeled containers.

Pick up excess with inert absorbent material

Keep away from drains and ground water.

7 HANDLING AND STORAGE

Handling Precautions:	Avoid contact with eyes, skin, or clothing. Keep away from sources of ignition. Do not pressurize, cut, weld, braze, solder, drill, or grind containers. Handle with care and avoid spillage on the floor (slippage). Ground and bond containers when transferring material
Storage Requirements:	Keep away from sources of ignition.

Store in a tightly closed container

SDS Number: 60982

9

11

Revision Date: 6/24/2019

Page 3 of 5

8	EXPOSURE CONTROLS/PERSONAL PROTECTION
Engineering Controls:	All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94).
Personal Protective Equipment:	Use of safety glasses and gloves is recommended.
Exposure Guidelines:	Light Aromatic Solvent Naphtha (Petroleum) OSHA TWA: 500 ppm 1,2,4-Trimethylbenzene ACGIH TWA: 25 ppm Xylene OSHA TWA: 100 ppm, 435 mg/m^3 Cumene OSHA TWA: 50 ppm, 245 mg/m^3mg/m^3 2-Butoxyethanol OSHA PEL: 50 ppm, 240 mg/m^3

PHYSICAL AND CHEMICAL PROPERTIES

SDS

Amber
Liquid
0.89 at 60 F (Water = 1)
Not available

Odor: Solubility: Freezing/Melting Pt.: Flash Point: Vapor Density: Bulk Density:

Hydrocarbon-like Nil in water Not available >46 C (>115 F) Not available 7.42 lbs/gal

10	STABILITY AND REACTIVITY
Chemical Stability:	Product is stable under normal conditions.
Chemical Stability:	Product is stable under normal conditions.
Conditions to Avoid:	High temperatures above 46 C (115 F), sparks, and open flame.
Materials to Avoid:	Avoid strong oxidizing agents. May burn or react violently to flourine/oxygen mixtures.
Hazardous Decomposition	on: Combustion will produce carbon dioxide and, possibly toxic chemicals such as carbon monoxide.
Hazardous Polymerizatio	on: Will not occur.

TOXICOLOGICAL INFORMATION

Acute Toxicity Light aromatic solvent naphtha (petroleum) LD50 Dermal Rabbit >3160 mg/kg LD50 Oral Rat 3492 mg/kg LC50 Inhalation, Vapor, Rat 6193 mg/m3 4 hours

1,2,4-Trimethylbenzene

LD50 Dermal Rabbit 3160 mg/kg LD50 Oral Rat 3400 to 6000 mg/kg LC50 Inhalation, Vapor, Rat 18000 mg/m³ 4 hours

SDS Number: 60982

Revision Date: 6/24/2019

Page 4 of 5

2-Butoxyethanol

LD50 Dermal Rabbit 220 mg/kg LD50 Oral Rat 470 mg/kg LC50 Inhalation, Vapor, Rat, 2175 4 hours

Sensitization None known. Germ Cell Mutagenicity None known. Carcinogenicity Cumene, IARC 2B Reproductive toxicity None known. Specific target organ systemic toxicity (repeated exposure) None known.

12	ECOLOGICAL INFORMATION
----	-------------------------------

Avoid exposing to the environment, no specific aquatic data available.

13 DISPOSAL CONSIDERATIONS

Dispose of waste material in accordance with all local, state/provincial, and national requirements Do not flush to surface water or drains

|--|

NA1993, -, Combustible liquid, n.o.s., PGIII, (Petroleum Naphtha, 1,2,4-Trimethylbenzene)

This material is not regulated for US DOT transportation in containers less than 119 gallons.

IMDG & IATA: UN1993, Flammable liquid, n.o.s., (Petroleum Naphtha, 1,2,4-Trimethylbenzene), 3, III.

15 REGULATORY INFORMATION

[%] RQ (CAS#) Substance - Reg Codes

[50-60%] Solvent naphtha, petroleum, light arom. (64742-95-6) TSCA

[<20%] 1,2,4-Trimethylbenzene (95-63-6) MASS, NJHS, PA, SARA313, TSCA, TXAIR

[<15%] 2-Butoxyethanol (111-76-2) HAP, MASS, OSHAWAC, PA, TSCA, TXAIR

[<2%] RQ(100LBS), Xylene (1330-20-7) CERCLA, CSWHS, EPCRAWPC, HAP, MASS, NJHS, OSHAWAC, PA, SARA313, TOXICRCRA, TSCA, TXAIR, TXHWL

[<1%] RQ(5000LBS), Cumene (98-82-8) CERCLA, HAP, MASS, NJHS, OSHAWAC, PA, PROP65, SARA313, TOXICRCRA, TSCA, TXAIR, TXHWL

TSCA: All components listed or exempt DSL: All components listed or exempt



This product can expose you to chemicals including Cumene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Regulatory Code Legend

RQ = Reportable Quantity TSCA = Toxic Substances Control Act MASS = MA Massachusetts Hazardous Substances List NJHS = NJ Right-to-Know Hazardous Substances PA = PA Right-To-Know List of Hazardous Substances

SDS Number: 60982

Revision Date: 6/24/2019

Page 5 of 5

SARA313 = SARA 313 Title III Toxic Chemicals TXAIR = TX Air Contaminants with Health Effects Screening Level HAP = Hazardous Air Pollutants OSHAWAC = OSHA Workplace Air Contaminants CERCLA = Superfund clean up substance CSWHS = Clean Water Act Hazardous substances EPCRAWPC = EPCRA Water Priority Chemicals TOXICRCRA = RCRA Toxic Hazardous Wastes (U-List) TXHWL = TX Hazardous Waste List PROP65 = CA Prop 65 DSL = Canadian Domestic Substances List

16 OTHER INFORMATION

The information contained in this Safety Data Sheet relates only to the specific material designated. Performance Diesel, LLC assumes no legal responsibility for use or reliance upon this data. This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Performance Diesel, LLC.

Revision Date: 6/24/2019