



251 KING MUIR ROAD
LAKE FOREST, ILLINOIS 60045

www.performance-diesel.com
lremensnyder@performance-diesel.com
847-565-8150

PERFORMANCE DIESEL, LLC
CHEMISTRY-DRIVEN PERFORMANCE

Technical Bulletin

Performance Antigel Deicer Formula

Application:

Performance Antigel Deicer Formula is a concentrated winter diesel and heating oil additive formulated to provide excellent winter operability of diesel, heating oil, bioheat and biodiesel blends.

Benefits:

- Provides maximum CFPP performance using Terpolymers and HWM
- Protects against fuel filter and line icing using non-alcohol jet fuel type deicer
- Provides excellent lubrication of all diesel fuel injection systems
- Provides excellent blending in cold diesel due to its additive pourpoint of -20F
- Effective in ULSD and Biodiesel blends up to B-20

Dosage Rate Recommendations:

Dosage Rate	CFPP Performance
1/3000	As low as -10F
1/1500	As low as -20F
1/750	< -30F

Typical Additive Characteristics:

Color: Light Yellow
Density: 7.46lbs/gal
Sulfur: 6.3 ppm
Additive Pour: -18.4F
Flash Point: 112F

Part #:	Package Size:
1005	5 gallon pail
1054	54 Gallon Drum
1325	325 Gallon Tote
1000	Bulk

This product complies with the US EPA 40 CFR 80.591 certification meaning product contains <15ppm (mg/L) sulfur product

PERFORMANCE DIESEL, LLC 847-565-8150 www.performance-diesel.com