

www.performance-diesel.com lremensnyder@performance-diesel.com 847-565-8150

Technical Bulletin

Performance Fuel Polisher Formula

Application:

Performance Fuel Polisher Formula is a multifunctional diesel additive formulated to be an integral part of a Tank Maintenance Program, with the other being an EPA Registered Biocide. Performance Fuel Polisher is effective in ULSD fuels including biodiesel blends.

Benefits:

- Breaks up Tank Sludge
- Disperses and removes water and oxidized contamination including microbial slime
- Reduces the freeze point of suspended water and effectively keeps fuel systems dry
- Prevents Thermal degradation of fuels and provides long term fuel stability

Dosage Rate Recommendations:

Dosage Rate	Performance Level
1/500	Tank Clean-Up with Biocide
1/1000	Maintenance (every 6 months)
1/3000	Fuel System/Tank Dryer/Deicer

Typical Additive Characteristics:

Color: Light Yellow Density: 7.43lbs/gal Sulfur Content: 6.1ppm Additive Pour: <-50F Flash Point: 124F

Part #:	Package Size:
6005	5 Gallon Pail
6054	54 Gallon Drum
6325	325 Gallon Tote
6000	Bulk

This product qualifies for the US EPA 40 CFR 80.591 certification, meaning product contains <15ppm (mg/L) sulfur